



Engineering & ConStruction



GRE CODE

GRE.EEC.R.99.CL.P.08602.12.114.00

PAGE

1 di/of 6

TITLE:

AVAILABLE LANGUAGE: EN

DATASHEET

Inverter

File: GRE.EEC.R.99.CL.P.08602.12.114.00

00	09/12/2021	ISSued	J.HEYL	S.LI	E.YUAN
			HUAW EI	HUAW EI	HUAW EI
REV.	DATE	DESCRIPTION	PREPARED	VERIFIED	APPROVED
GRE VALIDATION					
		M.FERRER		S.GARCIA	
COLLABORATORS		VERIFIED BY		VALIDATED BY	
PROJECT / PLANT		GRE CODE			
El Manzano		GROUP	FUNCION	TYPE	ISSUER
Chile		GRE	EEC	R	9
					9
					C
					L
					P
					0
					8
					6
					0
					2
					1
					2
					1
					1
					4
					0
					0
CLASSIFICATION		FOR VALIDATION		UTILIZATION SCOPE	
				ISSUED FOR CONSTRUCTION	
This dOcument IS prOperty Of Enel Green POWer S.p.A. It IS Strictly fOrbidden to rePrOduce thIS dOcument, in WhOle Or in part, and tO prOVide tO OtherS any related inFOrmatiOn WithOut the prEViOuS Written cOnSent by Enel Green POWer S.p.A.					



Engineering & ConStruction



GRE CODE

GRE.EEC.R.99.CL.P.08602.12.114.00

PAGE

2 di/of 6

INDEX

1. REFERENCES	3
2. MAIN CHARACTERISTICS.....	3
3. DC INPUT	3
4. AC OUTPUT.....	3
5. OTHERS	4
6. SUN2000-215KTL-H3 INVERTER DATASHEET (ANNEX).	4

1. REFERENCES

- ♦ GRE.EEC.S.27.XX.A.00000.00.156.08_TS-PV_Power_Plant.
- ♦ Physical Dimensions, Schematic and Layout (Protections included):
 - GRE.EEC.H.99.CL.P.08602.12.103.00 *Inverter* – Functional diagram and terminal blocks.
 - GRE.EEC.H.99.CL.P.08602.12.104.00 *Inverter* – External Wiring and Mechanical Diagram.
- ♦ Grounding:
 - GRE.EEC.D.99.CL.P.08602.12.107.00 *Inverter* - Grounding system layout and details
- ♦ SCADA:
 - GRE.EEC.R.99.CL.P.08602.12.108.00 Control System Network Architecture.
 - GRE.EEC.L.99.CL.P.08602.00.059.00 *Signal List of IED*
- ♦ Operation Principles:
 - SUN2000-(196KTL-H3, 200KTL-H3, 215KTL-H3) User Manual documentation.
- ♦ Inverter Appearance:
 - GRE.EEC.H.99.CL.P.08602.12.104.00 *Inverter* – External Wiring and Mechanical Diagram.
 - SUN2000-215KTL-H3 Datasheet.
- ♦ Energy Monitoring:
 - GRE.EEC.L.99.CL.P.08602.00.059.00 *Signal List of IED*
- ♦ Main Characteristics – DC Input & DC Input Protection / AC Output & AC Output Protection
 - GRE.EEC.S.99.CL.P.08602.12.109.00 *Inverter - Technical Specifications (according to EGP specification).*
- ♦ Inverter Characteristics complying Chilean Grid Code (NTSyCS)
 - GRE.EEC.S.99.CL.P.08602.12.109.00 *Inverter - Technical Specifications (according to EGP specification).*
- ♦ SUN2000-215KTL-H3 Harmonic Content.
 - GRE.EEC.S.99.CL.P.08602.12.109.00 *Inverter - Technical Specifications (according to EGP specification).*
- ♦ SUN2000-215KTL-H3 Characteristics Curves
 - GRE.EEC.S.99.CL.P.08602.12.109.00 *Inverter - Technical Specifications (according to EGP specification).*
- ♦ Output function:
 - GRE.EEC.S.99.CL.P.08602.12.109.00 *Inverter - Technical Specifications (according to EGP specification).*
 - GRE.EEC.R.99.CL.P.08602.12.126.00 *Inverter adjusted parameters report*

2. MAIN CHARACTERISTICS

- ◆ AC Electrical System Type: IT System.
- ◆ Auxiliary Consumption is taken from DC side, so it is already considered into the inverter efficiency curve.
- ◆ Stand by/Night consumption is 3.3 W.
- ◆ Static MPPT efficiency: 99.9% (>30% power load).
- ◆ Dynamic MPPT efficiency: 99%.
- ◆ Storage Temperature: -40°C to 70°C.
- ◆ Noise Level: Up to 65 dBA.

3. DC INPUT

- ◆ Max. DC Voltage Ripple: +.0.5%
- ◆ Reverse Polarity Protection is included.

4. AC OUTPUT

- ◆ According with IEC 60909, short-circuit contribution is the following:
 - ◆ $I_K = 155.2 \text{ A}$.
 - ◆ $I_P = 482.8 \text{ A}$.

- ◆ $I''_k = 232.8 \text{ A}$.
- ◆ Maximum current unbalancement: 2%

5. OTHERS

- ◆ Inverter AC waveform is made by 3 level PWM modulation adding a switching frequency of 18 [kHz].
- ◆ Shut off temperature is about 110°C on IGBT side. One temperature sensor is located in each IGBT module. After this, the relays installed into AC side of inverter will trip.
- ◆ Q at night feature is included as standard in SUN2000-185KTL-H1 inverter. More information can be founded into the document GRE.EEC.S.99.CL.P.08602.12.109.00 Inverter - Technical Specifications (according to EGP specification).

6. SUN2000-215KTL-H3 INVERTER DATASHEET (ANNEX).

SUN2000-215KTL-H3 Smart String Inverter



100A
Per MPPT



99.0%
Max. Efficiency



String-Smart
Switch



Smart I-V Curve
Diagnosis Supported



MBUS
Supported





Fuse Free
Design



Surge Arresters for
DC & AC



IP66
Protection



SUN2000-215KTL-H3

Technical Specifications

Efficiency	
Max. Efficiency	≥99.0%
European Efficiency	≥98.6%
Input	
Max. Input Voltage	1,500 V
Number of MPP Trackers	3
Max. Current per MPPT	100A/100A/100A
Max. PV Inputs per MPPT	4/5/5
Start Voltage	550 V
MPPT Operating Voltage Range	500 V ~ 1,500 V
Nominal Input Voltage	1,080 V
Output	
Nominal AC Active Power	200,000 W
Nominal Output Voltage	800 V, 3W + PE
Rated AC Grid Frequency	50 Hz / 60 Hz
Nominal Output Current	144.4 A
Adjustable Power Factor Range	0.8 LG ~ 0.8 LD
Max. Total Harmonic Distortion	< 1%
Protection	
Input-side Disconnection Device	Yes
Anti-islanding Protection	Yes
AC Overcurrent Protection	Yes
DC Reverse-polarity Protection	Yes
PV-array String Fault Monitoring	Yes
DC Surge Arrester	Type II
AC Surge Arrester	Type II
DC Insulation Resistance Detection	Yes
Residual Current Monitoring Unit	Yes
Communication	
Display	LED Indicators, WLAN + APP
USB	Yes
MBUS	Yes
RS485	Yes
General	
Dimensions (W x H x D)	1,035 x 700 x 365 mm (40.7 x 27.6 x 14.4 inch)
Weight (with mounting plate)	≤86 kg (191.8 lb.)
Operating Temperature Range	-25°C ~ 60°C (-13°F ~ 140°F)
Cooling Method	Smart Air Cooling
Max. Operating Altitude without Derating	4,000 m (13,123 ft.)
Relative Humidity	0 ~ 100%
DC Connector	Staubli MC4 EVO2
AC Connector	Waterproof Connector + OT/DT Terminal
Protection Degree	IP66
Topology	Transformerless